



YDPU2.E172592
Tubing, Extruded Insulating - Component

[Page Bottom](#)

Tubing, Extruded Insulating - Component

[See General Information for Tubing, Extruded Insulating - Component](#)

HOKKO CHEMICAL CO LTD
 7-5 ONO 3-CHOME
 NISHIYODOGAWA-KU
 OSAKA-SHI, OSAKA 555-0043 JAPAN

E172592

Cat. No.	Max V	Max Temp C	Col Recognized	Max Temp Rated Oil Resistance *,°C	VW-1 Rated #
Polyvinyl chloride (PVC) tubing.					
HIT-300V, HKI-300V	300	105	CL	80	Yes
HIT-300V, HKI-300V	300	105	All except CL	—	Yes
HIT-600V, HKI-600V	600	105	CL	80	Yes
HIT-600V, HKI-600V	600	105	All except CL	—	Yes

*Tubing is considered to comply with the optional oil resistant requirements only if it is so marked.

#Tubing is considered to comply with the optional VW-1 flammability requirements only if it is so marked.



Marking: Company name, tradename and/or trademark and catalog number, voltage rating, temperature rating in degrees C, inside diameter and VW-1 if complies, shall be marked on tags attached to both ends of the tubing, on the shipping spool label or on the smallest unit container.

[Last Updated](#) on 2009-08-14

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

© 2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".



YDPU8.E172592

Tubing, Extruded Insulating Certified for Canada - Component

[Page Bottom](#)

Tubing, Extruded Insulating Certified for Canada - Component

[See General Information for Tubing, Extruded Insulating Certified for Canada - Component](#)

HOKKO CHEMICAL CO LTD
7-5 ONO 3-CHOME
NISHIYODOGAWA-KU
OSAKA-SHI, OSAKA 555-0043 JAPAN

E172592


Cat. No.	Max V	Max Temp C	Col Recognized	Max Temp Rated Oil Resistance * C	VW-1 Rated #
Polyvinyl chloride (PVC).					
HIT-300V, HKI-300V	300	105	CL	60	Yes
HIT-300V, HKI-300V	300	105	All except CL	—	Yes
HIT-600V, HKI-600V	600	105	CL	60	Yes
HIT-600V, HKI-600V	600	105	All except CL	—	Yes

*Tubing is considered to comply with the optional oil resistant requirements only if it is so marked.

#Tubing is considered to comply with the optional VW-1 flammability requirements only if it is so marked.



Marking: Company name, tradename and/or trademark and catalog number, temperature rating in degrees C and voltage rating, inside

diameter and VW-1 if complies, and the Recognized Component Mark for Canada  on tags attached to both ends of the tubing or on the shipping spool label or smallest unit container.

Last Updated on 2009-08-14

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

© 2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".